

Instructions for Removing a Touch Screen Stereo/Head Unit from a 2022 Ford Transit Van

Follow these steps to safely and efficiently remove the touch screen stereo or head unit from the dashboard of a 2022 Ford Transit:

Tools Needed:

- Trim removal tools (plastic to avoid scratching)
 - Screwdrivers (Phillips and flathead)
 - Socket wrench with appropriate bits
 - A microfiber cloth to protect surfaces
 - Optional: Panel pry bar
-

Step-by-Step Process:

1. **Prepare the Area:**
 - Disconnect the negative terminal of the battery to prevent short circuits or damage to the electrical system.
 - Cover the seats and floor with a protective cloth to avoid scratches or stains.
 2. **Remove the Dashboard Bezel:**
 - Use a plastic trim removal tool to gently pry around the edges of the bezel surrounding the stereo.
 - Work slowly around the perimeter, unclipping the retaining tabs. Be careful not to force it to prevent breaking clips or cracking the bezel.
 3. **Detach AC and Vent Controls:**
 - If the AC controls or vents are integrated into the same bezel, disconnect their clips and electrical connectors. Use a trim tool to pop them out carefully.
 - Note how these connectors are attached for easier reassembly.
 4. **Unscrew the Stereo Unit:**
 - Once the bezel is removed, locate the screws securing the stereo to the dashboard. Typically, there are 4 screws at the corners.
 - Use the appropriate screwdriver or socket wrench to remove these screws and keep them in a safe place.
 5. **Slide Out the Stereo:**
 - Carefully pull the stereo out of the dash until the rear connectors are visible.
 - Be cautious to avoid snagging or pulling on the wires.
 6. **Disconnect Wiring:**
 - Detach the wiring harnesses and any antenna cables from the back of the stereo.
 - Some connectors may have tabs that need to be pressed or slid to release them.
 7. **Inspect and Store:**
 - Inspect all removed parts for damage.
 - Store the stereo and components in a safe location if they will be reused.
-

Tips for Reassembly:

- Ensure all connectors are firmly reattached and cables are routed safely to avoid pinching during reinstallation.
- Reinsert screws and tighten snugly, but do not overtighten to prevent stripping.
- Test the stereo and connected systems before fully reassembling the dash.